

	TBD 2025 production. Subject to material availability. "The January 2018 implementation of the new EPA Green House Gas Regulation, has been put off indefinitely. If at some future date the regulation is reinstated, it may require certain options to improve fuel efficiency and reduce emissions that are not included in this specification. Among these are low rolling resistance tires, aerodynamic devices, tire monitoring or inflation systems, and weight reduction. Orders that do not meet the requirements are subject to change orders and any cost increases that result."			
	SUBJECT TO Material Cost Review and SURCHARGE 90 days prior to QTR of production		Original Release	
Vanguard Stock	Workorder TM407961 SN TM407961 - TM408020		Revised 07/02/25	
				Weight
Quantity	60 units Model Year 2026	option		14158
Body Type	MaxCube	MaxCube		
Width	102-5/16"	std		
Length	53' 0" (52' 6" inside with swing doors, 52' 5" with OHD)	std		
Height	13' 6" (110" inside)	std		
Door Opening	110" tall x 99" wide	std		
Door Type	1/2" Composite pp white galvanized inner and outer panels	std		
Door Holdbacks	Rubber bumper on bottom hinge, chain and loop on door with hook recessed into base rail.	std		
Grabhandle	None	std		
Inside Width	101" post to post	MaxCube		
	47-3/16" with ultra high strength approach plate and 1/4" 67K bottom plate. Approach plate extends up front of trailer 2-1/4" creating approximately 1/2" thick fifthwheel impact area. Galvanized front lip.			
Upper Coupler Height		std		
King Pin Location	36"	std		
Tire / Wheel Size	295/75R22.5 / 8.25 x 22.5	std		
Tire Make	Cooper PRO Series LHT or Yokohama BE 109L FACTORY CHOICE radial. Smartway approved	new std		
Tire Inflation System	MTIS (Meritor Tire Inflation System)	option		18
Wheel Type	2HH disc powder coated white	std		
Hubo on Bracket	None	std		
Outboard Cast Drums	Webb Hub and Drum	option		
Number of Axles	Two	std		
Axle Make	As provided with suspension. Extended life brake lining. Tapered spindle.	std		
Wheel Seals	Stemco Seals	std		
Bearing Lubrication	HEARTLAND #0 SYN-POLY SEMI-FLUID GREASE	new std		
Spindle Nut	Zip Torq	std		
Hubcaps	NATIONAL HUBCAPS for MTIS	option		
Suspension	Holland CBX40 Air Ride Suspension 10 year warranty) with AiRelease (air assisted pin puller)	option		
Tandem Slide	49" spread 216" slide rails (72" to 174" slide range) (Note: Vanguard standard Holland slide rails specified with 6" center hole spacing with 1.56" hole diameter)	std		
Brake Size & Type	16.5" x 7" Air "S" - Cam	std		
Air Lines	3/8" diameter front to rear	std		
ABS	Bendix 2S1M ABS with SR5 spring brake release valve.	option		
Slack Adjusters	WABCO automatic (5 year limited warranty)	new std		
Brake Chambers	Haldux Gold Seal (4 year limited warranty) Includes brake stroke indicator.	std		
Landing Gear	Jost Magnum A450.G3.17.73 Galvanized bracing. 103" from KP. (10 yr warranty)	new std		
Landing Gear Crank Roadside	Yes	std		
Tire Carrier	No	std		
Crossmembers	4" I-Beams on 12" centers with 9" centers in bay. 7 crossmembers over landing gear. Aluminum squeeze rivets. 9mil black vinyl tape installed full height of base rail between crossmembers and base rail for electrolysis barrier.	option		210
X-member to Base Rail Attachment				
Floor	1-3/8" Rockland with Floor Saver 100% Oak with three 5/16" screws per board	std		
Threshold Plate	Heavy duty galvanized unitized forklift package and rear sill last 27" of trailer	std		
Scuff Band Sides	12" x 80KSI corrugated steel attached directly to side post	std		
Scuff Band Front	None	std		
Internal Bulkhead	10ga x 12" smooth steel attached directly to front wall posts	std		
Sidewall Liner	Impact resistant polypropylene recessed between posts with no fasteners	MaxCube		
Nose Liner	1/2" plywood full height with close out at bottom	std		
Ceiling Liner	None	std		
Side Panels	.050 aluminum pp white	std		
Side Posts	14ga x .531" MaxCube style series "A" logistic posts on 16" centers throughout	MaxCube		
Front Wall Panels	PPW Aluminum with 1/8" mill finish aluminum radius panels.	std		
Front Wall Posts	FIVE 2" deep hat section posts	std		
Roof Bows	1" deep galvanized steel anti-snap on 16" / 24" centers	std		
Roof Material	.040 Aluminum pre-bonded to bows prior to installation	std		
Rear Frame Color	GALVANIZED	std		
Midcam Lock	No	std		
Lock Rods per Door	One	std		
Hinges per Door	Five	std		
Rubber Dock Bumpers	One pair (4-hole) recessed between lights	std		
Rear Impact Guard (RIG)	Reinforced for Dock-Lock operation. GALVANIZED. (outboard verticals). Vanguard has earned the Insurance Institute for Highway Safety's TOUGHGUARD award for having a rear guard that helps to prevent underide of a midsize car traveling 35 MPH in three test modes — full-width, 50 percent overlap and 30 percent overlap. ALL RIG parts are bolt on.	std		
Flaps Mtd. to Slider	Yes 24" x 27-1/2" white antispray with Vanguard logo.	std		
	Optronics LED (Limited Lifetime Warranty) All Locations including license. Canada and California legal lights. Five lights rear header. Front and rear header lights with multi-function. GloLights at rear and mid-turn. Lower lights attached with aluminum closed end pop rivet for anti theft.			
Sealed Beam Lights		std		
Wiring Harness	Phillips split wiring harness with internal ground. (10 year warranty)	std		
7-Way Receptacle	Phillips Q-Box (split pin without circuit breakers). Non corrosive housing.	std		
	Phillips anodized with screens, non swivel type offset to roadside. REAR ACCESS MOUNT.			
Gladhands		new std		
Registration Holder	Truck-Lite 97960 or Phillips 16-802 or Optronics (factory choice)	std		
Manifest box	None	std		
Vents	None	std		
Logistic Track	None	std		
Placards	None	std		
Side Skirts	Ridge Greenwing Aerodynamic Skirt (RAC0012) BLACK	option		148
External Rub Rail	None	std		
	Pre-undercoated crossmembers and floor. Holland suspensions have Black Armour coating. Hendrickson suspensions have black soft coat. Slide rails are sprayed with undercoat and inside of coupler is sprayed.			
Undercoating		std		
Tracking System	NONE	std		
Customer Markings	None	std		
NOTE: The above specification is not designed or rated for "Sidewall Loading" such as carpet or tires. Improper loading will result in a reduced trailer life. Specifications to accommodate this type of loading are available from the factory upon request.				
			special	
	Vanguard standard specifications are subject to continuous engineering design improvements and may change without notice.	Price w/o FET		14534
	SUBJECT TO Material Cost Review and SURCHARGE 90 days prior to QTR of production	FET (estimate)		weight +/- 3%
CUSTOMER ACCEPTED		Price with FET		
			FOB Factory	